

Package: asleep (via r-universe)

September 18, 2026

Title Estimate Sleep from 'Accelerometry' Data

Version 0.3.0

Description Interfaces the 'asleep' python module
<<https://github.com/OxWearables/asleep>> from Yuan (2024)
<[doi:10.1038/s41746-024-01148-y](https://doi.org/10.1038/s41746-024-01148-y)> to estimate sleep from
'accelerometry' data.

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

Depends R (>= 4.1.0)

Imports assertthat, curl, lubridate, methods, readr, reticulate (>= 1.42.0), rlang

Suggests tidyr, dplyr, ggplot2, testthat (>= 3.0.0), callr

Config/testthat/edition 3

URL <https://github.com/jhuwit/asleep>, <https://jhuwit.github.io/asleep/>

BugReports <https://github.com/jhuwit/asleep/issues>

Config/roxygen2/version 8.0.0

Config/pak/sysreqs libpng-dev libssl-dev python3 libx11-dev

Repository <https://jhuwit.r-universe.dev>

Date/Publication 2026-08-19 18:23:46 UTC

RemoteUrl <https://github.com/jhuwit/asleep>

RemoteRef HEAD

RemoteSha fba138941ed405ab503f1f145f80697070ba0b2e

Contents

asleep	2
get_sslnet	4
have_asleep	5

py_require_asleep	5
sl_download_models	6
sl_read	6
sl_rename_data	7
Index	8

asleep	<i>Run asleep Model on Data</i>
--------	---------------------------------

Description

Run asleep Model on Data
Run asleep with Python

Usage

```
asleep(  
    file,  
    outdir = NULL,  
    min_wear_hours = 22L,  
    time_shift = "0",  
    report_light_and_temp = FALSE,  
    pytorch_device = c("cpu", "cuda:0"),  
    sample_rate = NULL,  
    verbose = TRUE,  
    force_download = FALSE  
)  
  
py_asleep(  
    ...,  
    pyenv_function = function() {  
        asleep::py_require_asleep()  
    },  
    show = FALSE  
)
```

Arguments

- | | |
|----------------|--|
| file | accelerometry file to process, including CSV, CWA, GT3X, and GENEActiv bin files |
| outdir | output directory for CSVs and outputs |
| min_wear_hours | Min wear time in hours to be eligible for summary statistics computation. The sleepnet paper uses 22 |
| time_shift | The number hours to shift forward or backward from the current device time. e.g. +1 or -1 |

report_light_and_temp	If true, it adds mean temp, and light columns to the predictions
pytorch_device	device to use for prediction for PyTorch.
sample_rate	Sample rate for the data, currently not used.
verbose	print diagnostic messages
force_download	force a download of the model, passed to <code>sl_download_models()</code>
...	arguments to pass to <code>asleep</code>
pyenv_function	function that loads the forest Python package. By default, it uses <code>reticulate::py_import("asleep")</code> to import the package. If this function has an <code>args</code> argument, the output of <code>pyenv_function</code> will be re-assigned to <code>args</code> .
show	Logical, whether to show the standard output on the screen while the child process is running, passed to <code>callr::r()</code>

Value

A list of outputs, including summaries, paths, and dataframes.

Examples

```
asleep_check_result = function() {
  res = try({suppressWarnings(asleep_check())})
  if (inherits(res, "try-error")) {
    res = FALSE
  }
  res
}

file = system.file("extdata/example_sleep.csv.gz", package = "asleep")
stopifnot(file.exists(file))
if (asleep_check_result()) {
  out = try({asleep(file = file, verbose = 2L)})
  if (inherits(out, "try-error")) {
    message(out)
    if (interactive()) {
      reticulate::py_last_error()
    }
  } else {
    pred = out$predictions
  }
}

file = system.file("extdata/example_sleep.csv.gz", package = "asleep")
df = readr::read_csv(file)
if (asleep_check_result()) {
  out = try({asleep(file = df)})
  if (inherits(out, "try-error")) {
    message(out)
  } else {
    st = out$predictions
  }
}
```

```

if (requireNamespace("ggplot2", quietly = TRUE) &&
    requireNamespace("tidyr", quietly = TRUE) &&
    requireNamespace("dplyr", quietly = TRUE)) {
  d = st[1:250,] |>
    dplyr::mutate(
      time = lubridate::as_datetime(time),
      time_end = dplyr::lead(time)
    ) |>
    dplyr::filter(!is.na(time_end))
  raw = df |> dplyr::filter(time >= min(d$time) & time <= max(d$time))
  dat = raw |>
    tidyr::gather(axis, value, -time)
  d = d |> dplyr::mutate(activity_y = as.numeric(sleep_wake == "sleep"))
  dat |>
    ggplot2::ggplot(ggplot2::aes(x = time, y = value, colour = axis)) +
    ggplot2::geom_step() +
    ggplot2::geom_segment(
      data = d,
      ggplot2::aes(
        x = time, xend = time_end,
        y = activity_y, yend = activity_y,
        linetype = sleep_wake
      ),
      colour = "black", linewidth = 1, inherit.aes = FALSE
    ) +
    ggplot2::labs(linetype = "Sleep/wake")
}
}
}

```

get_sslnet

Get SSL Net -

Description

Get SSL Net -

Usage

```
get_sslnet()
```

```
sl_get_sslnet()
```

Value

A keras model representing the SSL Net.

have_asleep	<i>Check the asleep Python Module</i>
-------------	---------------------------------------

Description

Check the asleep Python Module

Usage

```
have_asleep()

asleep_check(...)

asleep_version(...)
```

Arguments

... additional arguments to pass to [reticulate::py_list_packages](#)

Value

A logical value indicating whether the asleep Python module is available.

Examples

```
if (have_asleep()) {
  asleep_version()
}
```

py_require_asleep	<i>Command for py_require for asleep</i>
-------------------	--

Description

Command for py_require for asleep

Usage

```
py_require_asleep(...)
```

Arguments

... arguments to pass to [reticulate::py_require\(\)](#)

Value

A logical value indicating whether the package is available.

sl_download_models	<i>Download asleep models to Cache</i>
--------------------	--

Description

Download asleep models to Cache

Usage

```
sl_download_models(force_download = FALSE)
```

Arguments

`force_download` force a download of the model, even if it already exists at `model_path`

Value

A model from Python. `sl_download_model` returns a model file path.

sl_read	<i>Read a Data Set for asleep</i>
---------	-----------------------------------

Description

Read a Data Set for asleep

Usage

```
sl_read(file, resample_hz = "uniform", keep_pandas = FALSE)
```

Arguments

<code>file</code>	path to the file for reading
<code>resample_hz</code>	Target frequency (Hz) to resample the signal. If "uniform", use the implied frequency (use this option to fix any device sampling errors). Pass NULL to disable. Defaults to "uniform".
<code>keep_pandas</code>	do not convert the data to a <code>data.frame</code> and keep as a <code>pandas.data.frame</code>

Value

A list of the data and information about the data

Note

The data `P30_wrist100` is from <https://ora.ox.ac.uk/objects/uuid:19d3cb34-e2b3-4177-91b6-1bad0e0163e7>, where we took the first 180,000 rows, the first 30 minutes of data from that participant as an example.

Examples

```
file = system.file("extdata/example_sleep.csv.gz", package = "asleep")
if (asleep_check()) {
  out = sl_read(file, resample_hz = FALSE)
}
```

sl_rename_data	<i>Rename data for asleep</i>
----------------	-------------------------------

Description

Rename data for asleep

Usage

```
sl_rename_data(data)

sl_write_csv(data, path = tempfile(fileext = ".csv"))
```

Arguments

data	a data.frame of raw accelerometry
path	path to the CSV output file

Value

A data.frame of renamed columns

Index

asleep, [2](#), [3](#)
asleep_check (have_asleep), [5](#)
asleep_version (have_asleep), [5](#)

callr::r(), [3](#)

get_sslnet, [4](#)

have_asleep, [5](#)

py_asleep (asleep), [2](#)
py_require_asleep, [5](#)

reticulate::py_list_packages, [5](#)
reticulate::py_require(), [5](#)

sl_download_models, [6](#)
sl_download_models(), [3](#)
sl_get_sslnet (get_sslnet), [4](#)
sl_read, [6](#)
sl_rename_data, [7](#)
sl_write_csv (sl_rename_data), [7](#)